

## SWIMMING POOL PUMP SERIES



SP-12001



SP-1500

### APPLICATION AREA:

Swimming pool and spa pool.

### OPERATING LIMITS:

Trans medium's PH: 6-8.5  
Fluid temperature limit: 40°C  
Max ambient temperature: 75°C

### STRUCTURAL CHARACTERISTICS:

1. Insulation Class: class I
2. Protection Class: IP68

## SWIMMING POOL PUMP SERIES

PERFORMANCE CHART AT  $n=2900r/min$

MODEL	POWER		INLET/OUTLET	MAX.FLOW (L/min)	MAX.HEAD (m)	G.W (kg)	PACKING DIMENSION (mm)
	kW	HP					
SP-8001	0.45	0.6	1 1/2" X 1 1/2"	175	10	10	545*230*320
SP-10001	0.6	0.8	1 1/2" X 1 1/2"	210	12	10.2	545*230*320
SP-12001	0.9	1.2	1 1/2" X 1 1/2"	230	14	11	545*230*320
SP-15001	1.0	1.3	1 1/2" X 1 1/2"	250	15	11.5	545*230*320
SP-1100	1.1	1.5	3' ' X 3' '	300	16	15	635*300*398
SP-1500	1.5	2	3' ' X 3' '	335	17	17	635*300*398
SP-2200	2.2	3	3' ' X 3' '	450	20	20	635*300*398

